

## Optimizing Hybrid Fiber-Reinforced Composites With More Than Two Fibers For Pseudo-Ductile Behavior

Alexandre Correia<sup>(1)</sup>, Filipe Leal<sup>(1)</sup>, Rodrigo Tavares<sup>(2)</sup>, Fábio Conde<sup>(3)</sup>

<sup>(1)</sup>Instituto Superior Técnico, Portugal  
alexandre.miguel.correia@tecnico.ulisboa.pt; filipe.leal@tecnico.ulisboa.pt;

<sup>(2)</sup>Instituto de Engenharia Mecânica e Gestão Industrial (INEGI), Portugal  
rptavares@inegi.up.pt

<sup>(3)</sup>Instituto de Engenharia Mecânica (IDMEC), Portugal  
f.conde@campus.fct.unl.pt

**Keywords:** Genetic Algorithm, Hybridization, Fibrous Composites, Pseudo-ductility

**Abstract:** Unexplored techniques in the field of composites, in this case bringing together meta-heuristics and hybridization, provide a unique opportunity to achieve new optimal composite materials. Work on hybrid fibrous composites with more than two fibers is scarce, due to the complexity of micro-mechanical hybrid composites' models. Therefore, it is of paramount importance to explore solutions with new techniques if a new type of results is to be found. The scope of this work is to produce an adaptation of a model that reciprocates the failure mechanisms of composites, using known properties of fibers ([1]). It is intended to explore the potential of this level of hybridization adopting meta-heuristics, that open up a wider range of possible solutions. This problem reveals itself as multi-objective, considering not only pseudo-ductility as a parameter but also specifications such as how high is the baseline achieved by the material, on a stress-strain curve, and an additional criteria known as pseudo-plastic work . A computational model using genetic algorithms was developed to solve the optimization problem using either a weighted function approach or a multi-objective function with the purpose of identifying the Pareto Front. The obtained results point to a significant improvement on the project specifications when compared to the previous research on this particular subject ([2]). Both in house and commercial algorithms were tested and compared, yielding valuable results.

### References

- [1] R. P. Tavares, F. Otero, A. Turon, P. C. Camanho, *Effective simulation of the mechanics of longitudinal tensile failure of unidirectional polymer composites*, *International Journal of Fracture*, 208:269–285, December 2017.
- [2] F. M. Conde, P. G. Coelho, R. P. Tavares, P. C. Camanho, J. M. Guedes, H. C. Rodrigues, *Optimization of hybrid polymer composites under uniaxial traction*, *Engineering Computations*.